

## SUPER-FLEX SWING PIPE



### FEATURES

#### Super-Flex 100

- Superior flexibility allows pipe to be easily routed around hardscape, terraces, and uneven terrain to make installations as easy as possible.
- Textured surface makes product easier to handle, contributing to labor efficiency, especially under wet conditions.
- Quick and easy installation lowers material and labor costs.
- Manufactured from our proprietary Olefin Block Copolymer resin, featuring unique block architecture that allows for superior flexibility and less heat deflection which holds spiral barb fittings better than the competition.
- Compatible with all brands of spiral barb fittings.

### SPECS

- Inside diameter: 0.49" (1.24 cm)
- Operating pressure: Up to 80 psi (5.5 bar)
- Temperature: Up to 110°F (43°C)

PART NUMBER	MODEL	DESCRIPTION
SF100-005	Super Flex 100	Super Flex Swing Pipe, Compatible With All Spiral Barb Fittings

## SWING PIPE FITTINGS



### FEATURES

- Fittings are made of robust acetal material to ensure they can handle the most demanding job site applications.
- Easy twist-in insertion – no glue or clamps needed for installation.
- Aggressive barb lip makes a secure connection that helps eliminate leaks.

### SPECS

- Operating pressure: up to 80 psi (5.5 bar)
- Temperature: Up to 110°F (43°C)

PART NUMBER	MODELS	DESCRIPTION
1829-005	SFCPLG	½" barb x ½" barb coupling
1836-005	SFA050	½" MIPT x ½" barb adapter
1836-101	SFA075	¾" MIPT x ½" barb adapter
1813-074	SFE-075	¾" MIPT x ½" barb elbow
1813-005	SFE-050	½" MIPT x ½" barb elbow
1813-005	SB-TEE	½" barb x ½" barb x ½" barb tee